

VP-T42

Het innovatieve VoIP-telefoon toestel

De VP-T42 bevat verschillende innovatieve functies die speciaal ontworpen zijn voor het bedrijfsleven. Dit toestel streeft gebruiksgemak na tot in de kleinste details. Naast een rijke visuele ervaring, levert de VP-T42 ook een uitstekende geluidskwaliteit.



Optima
HD Voice



Gigabit



Paperless



Belangrijkste kenmerken en voordelen

Revolutionair nieuw design

Het ontwerp bevat onder andere een papiervrij design, non-slip rubberen voetjes en ergonomische verzonken knoppen.

HD Audio

De VP-T42 staat bekend om zijn uitstekende combinatie van hard- en software. Dankzij de 'wideband' technologie worden de akoestische prestaties gemaximaliseerd. In combinatie met tal van andere functies creëert dit toestel een geweldige face-to-face live ervaring.

Verbeterde call management

Met de zes flexibele toetsen op het beeldscherm kunnen er tot 15 verschillende productiviteitsverhogende functies worden geprogrammeerd. Bovendien kan dit toestel bediend worden met behulp van een draadloze hoofd-telefoon.

Kort en bondig

- ✓ HD Audio
- ✓ Revolutionair ontwerp
- ✓ Dual-port Gigabit Ethernet
- ✓ PoE-voeding
- ✓ 2,7" grafisch LCD-scherm
- ✓ Tot 3 SIP-accounts
- ✓ Papiervrij label design
- ✓ Headset aansluiting
- ✓ Mogelijkheid tot twee verschillende standen
- ✓ Wandbevestiging

VP-T42

Technische data

Audio feature

- HD voice: HD handset, HD speaker
- Wideband codec: G.722
- Narrowband codec: G.711(A/μ), G.723, G.729AB, G.726, GSM
- DTMF: In-band, Out-of-band(RFC 2833) and SIP INFO
- Full-duplex hands-free speakerphone with AEC
- VAD, CNG, AEC, PLC, AJB, AGC

Phone features

- 3 VoIP accounts
- One-touch speed dial, redial
- Call forward, call waiting, call transfer, call hold
- Call return, group listening
- Mute, auto answer, DND
- Call history: dialed/received/missed/forwarded
- 3-way conference call
- Direct IP call without SIP proxy
- Ring tone selection/import/delete
- Hotline, emergency call
- Set date time manually or automatically
- Dial plan, XML Browser, action URL

Directory

- Local phonebook up to 1000 entries
- Broadsoft contacts: custom/enterprise/personal/common/search/speed dial
- Black list
- XML/LDAP remote phonebook
- Intelligent search method
- Phonebook search/import/export

IP-PBX and BroadSoft Features

- Busy Lamp Field (BLF), BLF list
- Bridged Line Appearance(BLA)/SCA
- Anonymous call, anonymous call rejection
- DND & forward synchronization
- BroadWorks anywhere
- N-Way calling, remote office
- Network call logs

- BroadSoft call center features
- Message Waiting Indicator (MWI)
- Voice mail, call park, call pickup
- Intercom, paging, music on hold
- Call recording, hot-desking

Display and Indicator

- 2.7" 192x64-pixel graphical LCD with backlight
- LED for call and message waiting indication
- Dual-color (red or green) illuminated LEDs for line status information
- Intuitive user interface with icons and soft keys
- National language selection
- Caller ID with name, number

Feature keys

- 6 line keys with LED
- 6 line keys can be programmed up to 15 various features (3-page view)
- 5 features keys: message, headset, mute, redial, hands-free speakerphone
- 4 context-sensitive "soft" keys
- 6 navigation keys
- 2 volume control keys
- Illuminated mute key
- Illuminated headset key
- Illuminated hands-free speakerphone key

Interface

- Dual-port Gigabit Ethernet
- 1xRJ9 (4P4C) handset port
- 1xRJ9 (4P4C) headset port
- 1XRJ12 (6P6C) EHS port
- Power over Ethernet (IEEE 802.3af), Class 2

Other Physical Features

- Stand with 2 adjustable angles
- Wall mountable
- External universal AC adapter (optional): AC 100~240V input and DC 5V/1.2A output
- Power consumption (PSU): 1.4W-3.9W

- Dimension(W*D*H*T): 212mm*189mm*175mm*54mm
- Operating humidity: 10~95%
- Storage temperature: -10~50°C

Package Features

- Qty/CTN: 5 PCS
- N.W/CTN: 6.9 kg
- G.W/CTN: 7.6 kg
- Giftbox size: 241mm*236mm*138mm
- Carton Meas: 707mm*253mm*244mm

Management

- Configuration: browser/phone/auto-provision
- Auto provision via FTP/TFTP/HTTP/HTTPS for mass deploy
- Auto-provision with PnP
- BroadSoft device management
- Zero-sp-touch
- Provisioning server redundancy supported
- Reset to factory, reboot
- Package tracing export, system log

Network and Security

- SIP v1 (RFC2543), v2 (RFC3261)NAT transverse: STUN mode
- Proxy mode and peer-to-peer SIP link mode
- IP assignment: static/DHCP
- HTTP/HTTPS web server
- Time and date synchronization using SNTP
- UDP/TCP/DNS-SRV(RFC 3263)
- QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS DSCP
- SRTP for voice
- Transport Layer Security (TLS)
- HTTPS certificate manager
- AES encryption for configuration file
- Digest authentication using MD5/MD5-sess
- OpenVPN, IEEE802.1X
- IPv6

VP-T42

Visuele voorstelling

