

VP-W52P

De standaard draadloze oplossing


De VP-W52P is de standaard DECT oplossing van Voipplay waarmee er tot maximaal vier gelijktijdige gesprekken mogelijk zijn. Bovendien kunnen er in totaal vijf handsets aangesloten worden op het basisstation.



HD Voice



Up to 5 users



4 simultaneous calls

Belangrijkste kenmerken en voordelen

Basisfuncties

Bevat alle basisfuncties die men nodig heeft in een kmo zoals o.a. doorschakelen, handsfree bellen, wachtmuziek, een gedetailleerde gespreksgeschiedenis, het voeren van conferentiegesprekken,...

Langdurige batterij

Via 1 oplaadbeurt kunt u met dit toestel tot 10 uur bellen en blijft de telefoon tot 100 uur standby.

Kort en bondig

- ✓ HD audio
- ✓ Voeding via PoE
- ✓ 1.8" kleurendisplay
- ✓ Bereik binnen: 100m
- ✓ Bereik buiten: 300m
- ✓ Headset aansluiting
- ✓ Telefoonboek tot 500 contacten

VP-W52P

Technische data

Phone features

- Up to 5 VoIP accounts
- Handset select for receiving call
- Handset and Number select for making call
- Paging, intercom, auto answer
- Call hold, call transfer, 3-way conferencing
- Switching between calls
- Call waiting, mute, DND
- Caller ID display, redial
- Anonymous call, anonymous call rejection
- Call forward (always/busy/no answer)
- Speed dial, voicemail, silence
- Message Waiting Indication (MWI)
- Local phonebook for up to 500 entries
- (store in the base)
- Remote phonebook
- Phonebook search / import / export
- Call history (outgoing/missed/accepted)
- Direct IP call without SIP proxy
- Reset to factory, reboot
- Keypad lock, emergency call
- Dial Plan, music on hold
- Broadsoft directory, broadSoft Call Log
- Broadworks feature key synchronization
- Shared Call Appearance (SCA)

Personalisation

- 9 ringer melodies
- Screen saver, two kind of colour schemes
- Multiple languages

Management

- Auto-provision via FTP / TFTP / HTTP / HTTPS
- Auto-provision with PnPHandset upgrade: OTA (Over-The-Air)/USB port
- Configuration: browser / phone / auto-provision
- Trace package and system log export

Voice and codecs

- Full-duplex speakerphone
- Receiver volume control: 5 steps
- Ringer volume control: 5 steps+off
- Multiple advisory tones
- Acoustic warning for low battery status
- DTMF
- Wideband codec: G.722
- Narrowband codec: G.711 μ /A, G.723, G.726, G.729, iLBC
- VAD, CNG, AEC, PLC, AJB

Network features

- SIP v1 (RFC2543), v2 (RFC3261)
- SNTP/NTP
- VLAN (802.1Q and 802.1P)
- 802.1x, LLDP, PPPoE
- STUN Client (NAT Traversal)
- UDP, TCP
- IP assignment: static/DHCP

Security

- Open VPN
- Transport Layer Security (TLS)
- HTTPS (server / client)
- SRTP (RFC3711)
- Digest authentication using MD5
- Secure configuration file via AES encryption

Connectors

- CAT-iq2.0
- 1 x RJ45 10/100M Ethernet port
- Power over Ethernet (IEEE 802.3af)
- Headset jack (2.5 mm)
- A mini USB Port

Physical features

- Indoor Range: 20m~50m (The ideal distance is 50m)
- Outdoor Range: 300m (In ideal conditions)
- Standby Time: 100h (In ideal conditions)
- Talk Time: 5~10h (The ideal talk time is 10h)
- 1.8" 128x160 pixels color display
- Desktop or wall mountable
- LCD backlit, key backlit
- Energy-saving ECO mode/ECO Mode+
- 12 key numerical keypad, 5 navigation keys
- 2 softkeys, 6 function keys, 6 shortcut keys
- 3 LEDs on Base: 1 x power, 1 x Network, 1 x Call
- Base station: DC 5V / 600mA Output
- Charger: DC 5V / 600mA Output
- Phone size: 144mm x 50mm x 24mm
- Base station size: 153mm x 108mm x 45mm
- Operating humidity: 10 ~ 95%
- Operating temp: -10 ~ +50°C

Special features

- Increase range with up to 6 repeaters